


KENEX™ VEGA

HOMOGENEOUS VINYL

| DESCRIPTION | STANDARD | UNIT | RESULT |
|------------------------------|--|---------|----------------------------|
| Type of floor covering | ISO 10581 / EN 649 | - | Homogeneous Vinyl Flooring |
| Total thickness | ISO 24346 / EN 428 | mm | 2 |
| Width of sheet | ISO 24346 / EN 426 | m | 2 |
| Length of sheet | ISO 24346 / EN 426 | m | 20 |
| CLASSIFICATION | | | |
| European classification | ISO 10784 / EN 685 | class | 34-43 |
| Reaction to fire | EN 13501 - 1 | class | Bfl-s1 |
| | GB 8624 - 2012 | - | B1(B-s1,t0) |
| Toxic testing | GB 18586 - 2001 | - | Qualified |
| Static electrical propensity | EN 1815 | KV | ≤2 |
| Slip resistance | DIN 51130 | class | R9 |
| PERFORMANCES | | | |
| Type binder content | ISO 10581 / EN 649 | type | II |
| Dimensional stability | ISO 23999 / EN 434 | % | ≤0.4 |
| Residual indentation | ISO 24343-1 / EN 425 | mm | ≤0.1 (≈0.05) |
| Flexibility | ISO 24344 / EN 435 | - | No Cracking |
| Thermal conductivity | ISO 10456 / EN 12524 | W/(m.k) | ≈0.25 |
| Castor chair test | ISO 4918 / EN 425 | - | OK |
| Colour fastness to light | ISO 105 - B02 | degree | ≥6 |
| Chemical resistance | ISO 26987 / EN 423 | - | Very good |
| Bacteria resistance | ISO 846 - 2019 | - | Does not support growth |
| Surface treatment | MaxShield™ | | |
| Logistics information |  2mx20mx2.0mm  16 Rolls/Pallet  10Pallets/6400m ² | | |

ADVANTAGES



APPLICATION



*The sample is only used as a reference for color selection. The color may slightly different from the actual samples.

*The above technical parameters are typical test results under laboratory standard test conditions.

*If you have special requirements for a certain technical parameter, please discuss the specific details with our company when ordering.

